



Eco-Tuff™

High Traffic Coating

ET-121014.v1

DESCRIPTION: The perfect balance of the highest quality 100% Acrylic emulsion and Urethane dispersion with advanced bio-based technology that offers outstanding abrasion, hot tire pick-up, chemical, water, and weather resistance for interior or exterior use. It is a breathable self sealing, uniquely hard yet flexible coating. Eco-Tuff HT Coating may be topcoated with Eco-Tuff Clearcoats for sheen enhancements or as part of decorative and non skid aggregate applications. Use with Eco-Tuff Primers for your specific application.

Our industry changing bio-based chemistry makes high performance possible without toxic solvents or noxious lingering odors. Eco-Tuff not only meets the most stringent V.O.C. regulations, it is engineered with renewably sourced and recycled content, making it the most sustainable coating on the market today. Sustainability, performance and value are the cornerstones of the EcoProCote brand without compromise.



INTENDED USE: Properly profiled, clean and dry compatible surfaces: Concrete walkways, warehouse floors, garage floors, parking garage, wood decks, wood docks, fiberglass boat decks, and most primed metals. Suitable for interior and exterior use. Minimum 2 coats @ 6-8 wet mils per coat recommended.

SHEEN: Satin **NON-SKID OPTIONS:** Recycled 30 Mesh or 80 Mesh Glass Powders

COLOR OPTIONS: (12) Standard Pretinted or Color Pack Options in standard commercial grade or infrared reflective (I.R.) pigments. Custom colors available. **PACKAGING:** 1 Gallon, 5 Gallon, 55 Gallon, 275 Gallon Tote

The Smarter Option for High Traffic Areas!

- Resilient & Flexible • Excellent Flow & Adhesion
- Hard Wearing Chemistry • Work in Occupied Spaces
- Fast Return to Service • Most "LEED Potential"

TECHNICAL DATA:

V.O.C. Regulatory = 0 g/L
 Bio-Based Content = 17%
 Flash Point = Non Flammable
 Freeze Point = 32°F / 0°C
 Hazardous Components = None
 Protection A: Safety Glasses

INGREDIENT DISCLOSURE:

INGREDIENTS:	CAS#:
Acrylic-Urethane Co-Polymer	N/A (Non-Haz)
Bio-Based Emulsion	N/A (Non-Haz)
Water	7732-18-5
Solvent Free Surfactants	N/A (Non-Haz)
Solvent Free Wax Emulsion	N/A (Non-Haz)

NOTE: Normal application poses no hazard to the release of respirable dust, but grinding or sanding dried films of this product may yield respirable dust. Spraying the product will produce a respirable mist. In such cases, use proper safety precautions.

Solvent-Free Co-Polymers | NMP-Free | VOC-Free Glycol Ether Free | Virtually Odorless | Tough Barrier



250-300 Sq.Ft.
Per Gallon



Fast 1 Hour Dry
Time Typical



Surface Temp.
45°F-95°F

(Avoid exterior application if rain is in the forecast within 24 hours.)



Soap and water
clean-up.

Eco-Tuff™ High Traffic Coating	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	A

POTENTIAL USGBC LEED POTENTIAL: MR Credit 3- Materials Reuse, MR Credit 5- Regional Materials, MR Credit 6- Rapidly Renewable Materials, IEQ Credit 4- Low Emitting materials, ID Credit 1- Innovation in Design.



Made in the U.S.A.



Eco Safety Products

Phoenix, Arizona U.S.A.
Tel: (602)305-9397

www.ecosafetyproducts.com