

**Sustainable - Flexible - Durable**



**Eco-Tuff<sup>tm</sup>** is a single component, zero VOC, high build, high flex ultra tough waterproof coating material. The world's safest and most durable non-skid safety coating that delivers an attractive, long lasting finish on concrete, wood, metal, and fiberglass surfaces. There are no hazardous ingredients, is non-flammable and is virtually odorless.

**Eco-Tuff<sup>tm</sup>** is a one component water-based modified acrylic-urethane formulation that is easy to install, is self leveling and is easily repairable. It is engineered for the most extreme environments from freezing cold temperatures to the hottest climates around the world. It is capable of withstanding abrasion, UV, chemicals, hot tire pick-up, and submersible applications. The rubberized content provides a non-abrasive texture with excellent slip resistance in dry or wet conditions.



A minimum of two coats is recommended. It is suitable for both indoor and outdoor applications. Available in [17] standard colors with custom colors available. Choose from standard, enhanced flexibility, or submersible formulations.

- Green Building Compliant
- Recycled Content
- Non-Hazardous Ingredients
- Virtually Odorless
- Non-Flammable
- Rubberized Non Skid Coating
- High Build Abrasion Resistant Finish
- UV, Moisture, & Chemical Resistant
- Self Leveling & Bonding
- Easily Repairable Without Stripping

### **CSI Divisions:**

Division 3 - Concrete, 03 3500 Concrete Finishing, 03 4800 PreCast Concrete Specialities  
Division 9 - Finishes, 09 9400 Decorative Finishing, 09 6100 Flooring Treatment, 09 6700 Fluid Applied Flooring, 09 9600 High-Performance Coating, 09 9700 Special Coatings  
Division 7 - Thermal & Moisture Protection, 071900 Water Repellents

### **LEED Green Building Rating System:**

Materials & Resources:

Building Reuse, MR Credit 1

Local/Regional Materials, MR Credit 5

Recycled Content, MR Credit 6

Indoor Environmental Quality:

Low-Emitting Materials, EQ Credit 4

### **Technical Data:**

Approximate Spread Rate: 100-125 sq.ft./gal

Surface Temperature: 40° F -120° F

Dry to Touch: 1 hour

Intercoat: 1 hour (2 Coats Recommended)

Light Foot Traffic: 12-24 hours

Vehicular Traffic: 3-7 days

Full System Cure: 5-7 days

*Self leveling easy flow viscosity provides a uniform spread delivering a superior non abrasive non skid finish. ASTM Test Method C.O.F. Dry: .91 Wet: 1.29*

**Available At:**



Visit [www.ecoprocote.com](http://www.ecoprocote.com) for more product information or call (602)305-9397 for an **ecoprocote** dealer nearest you.