

Product Name:	Acri-Soy MST/Grout Sealer	Product Code:	A1-3002/A1-3003
Emergency Phone #:	1(877)366-7547	MSDS #:	MSDS.A1.0309.1
Eco Safety Products 2921 W. Culver Street, #4B Phoenix, Arizona 85009 U.S.A. www.ecoprocoat.com T: (602)305-9397 F: (602)305-6431	Health	0	
	Fire	0	
	Reactivity	0	
	Protection		
I. Identification			
Chemical Name:	Acri-Soy MST Sealer / Acri-Soy Grout Sealer		
Chemical Family:	Proprietary Soy-Based Mixture		
Chemical Formula:	Trade Secret		
DOT Information:	Not Regulated. Non Hazardous		
Notes:	No known chemical compounds listed as carcinogens under OSHA, ACGIH, NTP, IARC, California Prop 65, or Other.		
II. Composition Information on Ingredients			
Trade Secret:	Specific chemical identities will be made available to medical professionals and others as required by 29 CFR 1910.1200. (i) (iv). This product contains a non-hazardous mixture of a modified acrylic-soy ester emulsion.		
III. Hazards Identification			
<p>SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use so long as prescribed safety precautions are practiced. ACUTE EFFECTS OF OVEREXPOSURE: This product may be an eye and skin irritant. Contact with eye tissue may produce pain, watering, and/or burning sensation. Prolonged skin contact may irritate the skin. Ingestion of an excessive amount of the product may cause complications.</p>			
Eye Contact:	Slightly irritating. Does not injure eye tissue.		
Skin Contact:	Mild skin irritation is possible.		
Inhalation:	No known effects on respiratory tract.		
Ingestion:	No known chronic effects. May result in abdominal discomfort, nausea, and diarrhea.		
IV. First Aid Measures			
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If irritation develops, consult a physician.		
Skin Contact:	Flush contaminated skin with plenty of water. Consult a physician if irritation develops.		
Inhalation:	Move exposed person to fresh air. If irritation persists, get medical attention promptly.		
Ingestion:	Do not induce vomiting. If victim is conscious give plenty of water or milk to drink. Get medical attention immediately.		
V. Fire Fighting Measures			
Flammable Limits:	Not determined.		
Flash Point:	Not combustible.		
Extinguishing Media:	Dry chemical, foam, or water fog.		
Firefighting Procedures:	For precaution use self contained breathing apparatus.		
Fire and Explosion Hazards:	No unusual hazards are expected.		

Product Name:	Acri-Soy MST/Grout Sealer	Product Code:	A1-3002/A1-3003
Emergency Phone #:	1(877)366-7547	MSDS #:	MSDS.A1.0309.1
Eco Safety Products 2921 W. Culver Street, #4B Phoenix, Arizona 85009 U.S.A. www.ecoprocoat.com T: (602)305-9397 F: (602)305-6431	Health		0
	Fire		0
	Reactivity		0
	Protection		
VI. Accidental Release Measures			
May be slippery when wet. Use caution during cleanup. Squeegee or broom spilled material and dispose in accordance with all local, state and federal regulations. Spills may be absorbed by an absorbent material and dispose as solid waste according to your local, state and federal regulations.			
VII. Handling and Storage			
Store material in a cool, dry and well ventilated area between 40°F-90°F. Keep containers closed and air tight. Avoid freezing.			
VIII. Exposure Controls and Personal Protection			
Ventilation:	General local ventilation, no special precautions.		
Eye Protection:	Wear safety goggles. Protect plastic lenses.		
Gloves:	Wear protective gloves to avoid possible skin irritation.		
Clothing:	Wash clothing after use.		
Wash Requirements:	Wash with soap and water.		
Respirator:	None required. Wear protective mask if spraying material and mist exceeds acceptable levels.		
IV. Physical and Chemical Characteristics			
Boiling Point:	>212°F/100°C	Vapor Pressure (mm Hg):	Not Determined
Vapor Density (Air = 1):	Not Determined	Solubility in Water:	Soluble
Specific Gravity (H ₂ O = 1):	1	Melting Point:	Not Determined
Evaporation Rate (H ₂ O = 1):	1	Appearance:	Slightly Milky White
Odor:	Mild	Freezing Point:	15°-20°F/-9.44°--6.66°C
V.O.C. Content:	0	Auto Ignition:	No
X. Stability and Reactivity			
Stability:	Stable		
Conditions to Avoid:	None known		
Hazardous Decomposition:	None known		
Hazardous Polymerization:	None known		
XI. Toxicological Information			
Route of Entry:	Inhalation. Skin. Eyes.		
Toxicological:	Eye irritant. This product does not contain any ingredient designated by IARC, NTP, ACGIH, or OSHA, as probable or suspected human carcinogens		
XII. Ecological Information			
Aquatic toxicity rating not determined. All possible measures should be taken to prevent release into the environment.			



MATERIAL SAFETY DATA SHEET

Product Name:	Acri-Soy MST/Grout Sealer	Product Code:	A1-3002/A1-3003
Emergency Phone #:	1(877)366-7547	MSDS #:	MSDS.A1.0309.1
Eco Safety Products 2921 W. Culver Street, #4B Phoenix, Arizona 85009 U.S.A. www.ecoprocoat.com T: (602)305-9397 F: (602)305-6431	Health	0	
	Fire	0	
	Reactivity	0	
	Protection		
XIII. Disposal Information			
Disposal of product must be in accordance with all federal, state, and local regulations.			
XIV. Transport Information			
Not Regulated			
XV. Regulatory Information			
Toxic Substances Control Act (TSCA): This product does not contain ingredients subject to reporting of TSCA 12 (B) if exported from the United States.			
OSHA Hazard Communication Standard (29 CFR 1910.1200): Not Hazardous.			
California Prop 65: To the best of our knowledge, this product does not contain ingredients on the Prop 65 substance list, which the state of California has found to cause cancer, birth defects, or other reproductive effects.			
International Regulations: Consult the regulations of the applicable country of import.			
XVI. Other Information			
THE INFORMATION GIVEN AND RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. ALL SUCH INFORMATION IS BELIEVED TO BE TRUE AND ACCURATE TO THE BEST OF OUR KNOWLEDGE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THE OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.			